

# Bullseye Rapid-Set Safe Deposit Lock

Interchangeable with most 3175 Series  
and all 5700 Series locks



1-800-364-4899 [bullseyesdlocks.com](http://bullseyesdlocks.com)



3175 Series locks



5700 Series locks

## Lock Description

The 3175 Rapid-Set lock is a service replacement lock manufactured with the guard lever biting set to NEUTRAL. The lock, as received from the factory, will operate with a Neutral Guard Key, until the guard lever biting sequence is "set" at the installation site to an active guard key. The 3175 Rapid-Set lock can be "set" to any existing 3175 and most existing FLAT 5700 guard key biting sequences, provided the biting sequence is factory cut on a corrugated 3175 GUARD KEY BLANK. The lock can be "set" only once (unless all the guard levers are manually reset to the neutral position). Once the lock is "set" to an active guard key, the Neutral Guard Key will no longer operate the lock.

1. Insert the neutral guard key (Part No. M00417); into the guard nose and turn the key counter-clockwise to stop.
2. Insert the renter key into the renter nose and turn the key clockwise until the lock bolt is fully retracted.
3. Turn the neutral guard key clockwise and remove.
4. Do not remove the renter key - leave the renter key in the unlocked position with the bolt retracted.
5. Insert a factory cut Rapid-Set guard key into the guard nose and turn the key counter-clockwise to stop. Cycle the guard key back and forth through 60 degrees (clockwise and counter-clockwise) three or four times to ensure that the guard levers have been properly set.
6. Remove both keys and then retest the lock several times for proper operation.